

OPIS IZDELKA:		MAST K1
SESTAVA: ŽIVALSKI STRANSKI PROIZVOD – ŽSP K1		
max. dovoljene vsebnosti	vrsta snovi	%
kakovostni parametri	FFA	< 20
	NETOPNE NEČISTOČE	< 0,15
		max mg/kg
	Polietilen	1.200
	Fosfor (P)	500
	Kalcij (Ca)	500
	Žveplo	20
	GTH	250
SESTAVA	topljene maščobe pridobljene iz ŽSP K1	
PRIPRAVA	Sterilizacija odpadkov, sušenje, stiskanje, čiščenje masti	
PAKIRANJE	Razsuto, v skladiščnih cisternah	
PAKIRANJE	Pri temperaturi 80°C v skladiščnih cisternah	
DISTRIBUCIJA	Z avtocisternami (T>50°C)	
ROK TRAJANJA	ni omejen	
UPORABA	Energetski odpadek, primeren za sežig, biodiesel	
CILJNE SKUPINE	Sežigalnice odpadkov, toplarne, kotlovnice, biodiesel	
PRODUCT DESCRIPTION:		ANIMAL FAT Cat 1
COMPOSITION: ANIMAL BY PRODUCTS – ABP CAT_1		
Max. Permitted contain	Substances	%
Quality parameters	FFA	< 20
	INSOLUBLE IMPURITIES	< 0,15
		max mg/kg
	Polyethylene	1.200
	Phosphorus (P)	500
	Phosphorus (P)	500
	sulfur	20
	GTH	250
COMPOSITION:	Renderd fats obtained from the ABP K1	
PREPARING:	Sterilization, drying, pressing, fat cleaning	
PAKIRANJE	Bulk, in storage tanks	
STORAGE:	At a temperature of 80 ° C in storage tanks	
DISTRIBUTION:	transportation by road tankers (temperature> 50 ° C)	
SHELF LIFE:	not specified	
APPLICATION:	Energy waste suitable for incineration, biodiesel	
TARGET GROUP:	Waste incineration plants, boilers, biodiesel	